

















IBR 890 (Supa-Clad) Standard Flashings

<p>Internal Corner Girth 462mm</p>  <p>FS1</p>	<p>External Corner Girth 462mm</p>  <p>FS2</p>	<p>Ridge Cap Girth 462mm</p>  <p>FS3</p>	<p>Hip Cap Girth 462mm</p>  <p>FS3a</p>
<p>Barge Flash Girth 462mm</p>  <p>FS4</p>	<p>Apex Flash Girth 462mm</p>  <p>FS5</p>	<p>Drip Flash Girth 231mm</p>  <p>FS6</p>	<p>Counter Flash Girth 185mm</p>  <p>FS7</p>
<p>Headwall Flash Girth 308mm</p>  <p>FS8</p>	<p>Sidewall Flash Girth 308mm</p>  <p>FS9</p>	<p>Sill Flash Girth 154mm</p>  <p>FS10</p>	<p>Door Jamb Girth 231mm</p>  <p>FS11</p>
<p>Window Jamb Girth 231mm</p>  <p>FS12</p>	<p>Roll Top Ridge Girth 462mm</p> 	<p>Roll Top Valley Girth 462mm</p> 	<p>Valley Gutter Girth 462mm</p> 

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -

ie. : Brownbuilt ridge cap FB3, 150 deg. angle

SB designates "Standard Bend", for which there is no charge

Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225