

















# Nu-Rib Standard Flashings

<p><b>Ridge Cap</b> Girth 462mm</p> 	<p><b>Hip Cap</b> Girth 462mm</p> 	<p><b>Gable / Barge</b> Girth 462mm</p> 	<p><b>Gable / Barge</b> Girth 385mm</p> 
<p><b>Internal Corner</b> Girth 462mm</p> 	<p><b>External Corner</b> Girth 462mm</p> 	<p><b>Headwall Flash</b> Girth 308mm</p> 	<p><b>Sidewall Flash</b> Girth 308mm</p> 
<p><b>Counter Flash</b> Girth 154mm</p> 	<p><b>Apex Flash</b> Girth 462mm</p> 	<p><b>Valley</b> Girth 462mm</p> 	<p><b>Valley Gutter</b> Girth 616mm</p>  <p style="text-align: center;">Included Angle = °</p>
<p><b>Drip Flash</b> Girth 154mm</p> 	<p><b>Door Jamb</b> Girth 154mm</p> 	<p><b>Window Jamb</b> Girth 154mm</p> 	<p><b>Sill Flash</b> Girth 154mm</p> 

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -  
 ie. : Nu-Rib ridge cap, 150 deg. angle  
 SB designates "Standard Bend", for which there is no charge

## Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225