

Klip-lok 700 Standard Flashings

<p>Internal Corner Girth 616mm</p> <p>FK71</p>	<p>External Corner Girth 616mm</p> <p>FK72</p>	<p>Ridge Cap Girth 550mm</p> <p>FK73</p>	<p>Hip Cap Girth 550mm</p> <p>FK73a</p>
<p>Barge Flash Girth 580mm</p> <p>FK74</p>	<p>Apex Flash Girth 550mm</p> <p>FK75</p>	<p>Drip Flash Girth 231mm</p> <p>FK76</p>	<p>Counter Flash Girth 185mm</p> <p>FK77</p>
<p>Headwall Flash Girth 375mm</p> <p>FK78</p>	<p>Sidewall Flash Girth 408mm</p> <p>FK79</p>	<p>Sill Flash Girth 185mm</p> <p>FK710</p>	<p>Door Jamb Girth 308mm</p> <p>FK711</p>
<p>Window Jamb Girth 308mm</p> <p>FK712</p>	<p>Barge (Roof Only) Girth 580mm</p> <p>FK713</p>	<p>Apex (Roof Only) Girth 550mm</p> <p>FK714</p>	<p>Valley Gutter Girth 610mm</p> <p>FK715</p>

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -

ie. : Brownbuilt ridge cap FB3, 150 deg. angle

SB designates "Standard Bend", for which there is no charge

Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225