

# Corrugated 10.5 Standard Flashings

<p><b>Roll Top Ridge</b> Girth 462mm</p>	<p><b>Ridge Cap</b> Girth 462mm</p>	<p><b>Roll Top Hip</b> Girth 462mm</p>	<p><b>Hip Cap</b> Girth 462mm</p>
<p><b>Gable / Barge</b> Girth 462mm</p>	<p><b>Gable / Barge</b> Girth 385mm</p>	<p><b>Internal Corner</b> Girth 462mm</p>	<p><b>External Corner</b> Girth 462mm</p>
<p><b>Headwall Flash</b> Girth 308mm</p>	<p><b>Sidewall Flash</b> Girth 308mm</p>	<p><b>Counter Flash</b> Girth 154mm</p>	<p><b>Apex Flash</b> Girth 462mm</p>
<p><b>Roll Top Valley</b> Girth 462mm</p>	<p><b>Valley</b> Girth 462mm</p>	<p><b>Valley Gutter</b> Girth 616mm</p> <p>Included Angle = °</p>	

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -

ie. : Corrugated ridge cap, 150 deg. angle

SB designates "Standard Bend", for which there is no charge

## Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225