















# Zip-Tek 420 Standard Flashings

<p><b>Internal Corner</b> Girth 656mm</p>  <p>ZT1</p>	<p><b>External Corner</b> Girth 656mm</p>  <p>ZT2</p>	<p><b>Ridge Cap</b> Girth 462mm</p>  <p>ZT3</p>	<p><b>Hip Cap</b> Girth 462mm</p>  <p>ZT3a</p>
<p><b>Barge Flash</b> Girth 600mm</p>  <p>ZT4</p>	<p><b>Apex Flash</b> Girth 512mm</p>  <p>ZT5</p>	<p><b>Drip Flash</b> Girth 269mm</p>  <p>ZT6</p>	<p><b>Counter Flash</b> Girth 185mm</p>  <p>ZT7</p>
<p><b>Headwall Flash</b> Girth 331mm</p>  <p>ZT8</p>	<p><b>Sidewall Flash</b> Girth 428mm</p>  <p>ZT9</p>	<p><b>Sill Flash</b> Girth 230mm</p>  <p>ZT10</p>	<p><b>Door Jamb</b> Girth 365</p>  <p>ZT11</p>
<p><b>Window Jamb</b> Girth 330mm</p>  <p>ZT12</p>	<p><b>Valley Gutter</b> Girth 610mm</p>  <p>ZT13</p>		

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -  
 ie. : Zip-Tek ridge cap ZT3, 150 deg. angle  
 SB designates "Standard Bend", for which there is no charge

## Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225

**Note**  
 The above standard flashings are estimated requirements only, and it is the clients responsibility to check and ensure that the dimensions etc. are suitable for their particular application before ordering.