















Zip-Tek 440 Standard Flashings

<p>Internal Corner Girth 656mm</p>  <p>ZT1</p>	<p>External Corner Girth 656mm</p>  <p>ZT2</p>	<p>Ridge Cap Girth 462mm</p>  <p>ZT3</p>	<p>Hip Cap Girth 462mm</p>  <p>ZT3a</p>
<p>Barge Flash Girth 600mm</p>  <p>ZT4</p>	<p>Apex Flash Girth 512mm</p>  <p>ZT5</p>	<p>Drip Flash Girth 269mm</p>  <p>ZT6</p>	<p>Counter Flash Girth 185mm</p>  <p>ZT7</p>
<p>Headwall Flash Girth 331mm</p>  <p>ZT8</p>	<p>Sidewall Flash Girth 428mm</p>  <p>ZT9</p>	<p>Sill Flash Girth 230mm</p>  <p>ZT10</p>	<p>Door Jamb Girth 365</p>  <p>ZT11</p>
<p>Window Jamb Girth 330mm</p>  <p>ZT12</p>	<p>Valley Gutter Girth 610mm</p>  <p>ZT13</p>		

Quote code and angle (where applicable) when ordering to ensure correct flashing is supplied -

ie. : Zip-Tek ridge cap ZT3, 150 deg. angle

SB designates "Standard Bend", for which there is no charge

Flashings Girth Sizes

When designing a non-standard flashing or, flashings of your own design, please note the standard girths (total width of material) indicated to the right.

Note

The above standard flashings are estimated requirements only, and it is the clients responsibility to check and ensure that the dimensions etc. are suitable for their particular application before ordering.

GIRTH MM
0 to 154
155 to 231
232 to 308
309 to 385
386 to 462
463 to 540
541 to 616
617 to 770
771 to 925
926 to 1225