

Bond-Dek

Item	Description	Unit	Quantity	Rate	Total
1.	<p>The permanent form work shall be Bond-Dek , 75mm deep x 900mm wide rib trough interlocking sheets roll-formed from certified steel complying with ASTM 446 Grade C with Z275 Galvanised finish or Black Supa-Form CR300 steel.</p> <p>Manufacturer: Global Roofing Solutions</p> <p>Tel.(011)898-2900</p> <p>Options of finish to be placed above:</p> <ul style="list-style-type: none"> • 0.8mm Galvanized Z275 Spelter • 1.0mm Galvanized Z275 Spelter. • 1.2mm Galvanized Z275 Spelter. • 0.8mm Black Supa-Form CR300 steel • 1.0mm Black Supa-Form CR300 steel • 1.2mm Black Supa-Form CR300 steel 	M2			
2.	Kerb Flashing 25 x 75 x slab depth. Available in 0.8mm, 1.0mm, 1.2mm Z275 Spelter Galvanized steel.	Lm			
3.	Drip Kerb Flashing 25 x 25 x 35 x 50 x Depth of slab available in 0.8mm, 1.0mm, 1.2mm Z275 Spelter Galvanized Steel.	Lm			
4.	Strapping to secure flashing	Lm			
5.	Bond-Dek closer	Lm			